

HP

Up to 100 mm Ø, 100 W – 12 000 W



KEY FEATURES

- 1. HIGH POWER HANDLING**
Handles up to 12 kW of continuous power with our standard models. Custom models available for higher powers (See SUPER HP)
- 2. STABLE READING**
Less sensitive to variations in water cooling temperature than any other high power water-cooled meter on the market
- 3. LARGE APERTURE**
Our standard HP models (4kW and 12kW) have a very large effective aperture of 100 mm Ø to accommodate large laser beams. Larger apertures with various shapes are available upon request (See SUPER HP)
- 4. SPECIAL MODEL FOR SMALL BEAMS**
10 kW model with reflective cone available. Perfect for small beams (with Avg Power Densities up to 10 kW/cm² @ 10 kW)
- 5. AVAILABLE WITH YAG AND CO₂ CALIBRATIONS**
All HP Models can be calibrated at YAG and CO₂ wavelengths with a calibration uncertainty of ± 2.5%
- 6. DIRECT USB CONNECTION TO A PC**
Each head comes with both a DB-15 connector (for use with a Gentec-EO monitor) and a USB2.0 output for direct connection to a PC

AVAILABLE MODELS



HP100A-4KW-HE
(4000W-Water-Cooled)



HP100A-12KW-HD
(12000W-Water-Cooled)



HP60A-10KW-GD
(10000W-Small Beams)

ACCESSORIES



Stand with Steel Post
(Model Number: 201102)



Extension Cables
(4, 15, 20 or 25 m)



5 m USB Cable
(Included)



Pelican Carrying Case

SEE ALSO

HOW IT WORKS	14
CALIBRATION	6
TECHNICAL DRAWINGS	106
COMPATIBLE MONITORS	
MAESTRO	20
TUNER	24
UNO	26
S-LINK	28
P-LINK	30
M-LINK	32
LIST OF ALL ACCESSORIES	186
APPLICATION NOTE	
MEASURING IN VACUUM	202178

MONITORS

ENERGY DETECTORS

POWER DETECTORS

HIGH POWER SOLUTIONS

PHOTO DETECTORS

THZ DETECTORS

OEM DETECTORS

SPECIAL PRODUCTS

BEAM DIAGNOSTICS

HP



*Also traceable to NRC-CNRC

SPECIFICATIONS

	HP100A-4KW-HE	HP100A-12KW-HD	HP60A-10KW-GD
MAX AVERAGE POWER (CONTINUOUS / 2 MINUTES)	4 000 W / 4 500 W	12 000 W / 12 000 W	10 000 W / 10 000 W High Average Power up to 10 kW/cm ²
EFFECTIVE APERTURE	100 mm Ø	100 mm Ø	60 mm Ø with cone reflector
COOLING METHOD	Water-Cooled	Water-Cooled	Water-Cooled
MEASUREMENT CAPABILITY			
Spectral Range	0.19 – 20 µm	0.19 – 20 µm	0.8 – 12 µm
Noise Equivalent Power ^a	±3 W	±10 W	±10 W
Minimum Average Power ^b	100 W	300 W	300 W
Rise Time (nominal)	7 sec	9 sec	11 sec
Sensitivity (typ into 100 kΩ load)	0.4 mV/W	0.15 mV/W	0.2 mV/W
Calibration Uncertainty	±5 % @ 1064 nm	±5 % @ 1064 nm	±5 % @ 1064 nm
Repeatability	±2 %	±2 %	±2 %
Linearity with Power	±1.5 %	±1.5 %	±2 %
Linearity vs Beam Diameter	±1 %	±1 %	< 35 mm Ø: ±0.5 % > 35 mm Ø: ±1.5 %
Linearity vs Beam Position	±1.5 %	±1.5 % ^c / ±3 % ^d	±3 %
DAMAGE THRESHOLDS			
Maximum Average Power Density ^e			
500 W	10 kW/cm ²	16 kW/cm ²	---
4 kW	4 kW/cm ²	---	---
5 kW	---	6.5 kW/cm ²	---
10 kW	---	3.5 kW/cm ²	< 35 mm Ø: 10 kW/cm ² > 35 mm Ø: 3.5 kW/cm ²
PHYSICAL CHARACTERISTICS			
Effective Aperture	100 mm Ø	100 mm Ø	60 mm Ø (Optimized for 35 mm Ø)
Absorber (High Damage Threshold)	HE	HD	GD (cone reflector)
Required Cooling Flow	(4 - 6) LPM < ±1 LPM/min ^f	(6 - 10) LPM < ±1 LPM/min ^f	(6 - 10) LPM < ±1 LPM/min ^f
Temperature of Cooling Water	(15 - 25) °C < ±3°C/min ^f	(15 - 25) °C < ±3°C/min ^f	(15 - 25) °C < ±3°C/min ^f
Output Connectors	DB-15 cable & USB port	DB-15 cable & USB port	DB-15 cable & USB port
PCB Electrical Supply	Through USB or Gentec-EO monitors	Through USB or Gentec-EO monitors	Through USB or Gentec-EO monitors
Maximum Output Signal	2 V	2 V	2 V
Dimensions	127H x 127W x 74D mm	127H x 127W x 70D mm	127H x 127W x 90D mm
Weight (head only)	1.8 kg	3.3 kg	5 kg
ORDERING INFORMATION			
Product Name	HP100A-4KW-HE	HP100A-12KW-HD	HP60A-10KW-GD
Product Number (including stand)	202208	201329	201306

Specifications are subject to change without notice

- a. Nominal value, actual value depends on electrical noise in the measurement system.
 b. For lower powers, call your Gentec-EO representative.
 c. For a beam size of 10% of the aperture area, moved across 40% of the aperture area.
 d. For a beam size of 20% of the aperture area, moved across 80% of the aperture area.
 e. At 1064 nm, 1.07-1.08 µm and 10.6 µm.
 f. > 1 min. Contact Gentec-EO for clean deionized water cooling module option.